



MAXIBOND LATEX MULTIPURPOSE LATEX ADMIXTURE

上等级牛奶水

MAXIBOND LATEX is a multipurpose premium grade latex admixture specially formulated for use with cement based tile adhesive, tile grout, cement or cement-sand mortar. It will substantially improve the adhesion strength, water resistance, wear resistance and workability of the cement mixes. It is ideal for installation of wall and floor tiles (interior/exterior), stones for internal & external facade, swimming pool etc. it is also use to mix with cement -sand to improve the adhesion strength of cement mortar renders, floor screed, repair mortars etc.

ADVANTAGES

- ▲ Extremely good bonding and adhesion.
- ▲ Reduced shrinkage, increased flexural and tensile strength.
- ▲ Excellent water resistance.
- ▲ Improved resistance to acid/chemical.

USAGE & APPLICATION

- ▲ Use with cement-based Tile Adhesive for internal and external tiling works.
 - Dosage: 6-8 Litre per 25kg Tile Adhesive.
- ▲ Use with cement-based Colored Grout.
 - Dosage: 1-1.5 Litre per 3.5kg Colored Grout.
- ▲ Use with cement-sand to prepare Slurry Bonding Agent.
 - Mixing Ratio : 1 part Maxibond Latex
: 2 parts cement
- ▲ Use with cement-sand to prepare Latex Modified Renders or Screed and Repair Mortar.
 - Dosage: 8-15 Litres per 50kg cement sand mix.