



## DURACEM FLEXI SEALER FLEXIBLE WATERPROOF SEALER

# 防水护膜

**DURACEM FLEXI SEALER** is a ready-mixed acrylic copolymer latex coating specially formulated for sealing cracks and joints on walls, ceilings and roofs by forming a tough continuous waterproof membrane. This thin membrane is exceptionally flexible, durable and weather resistant when dry.

### DIRECTION FOR USE

**DURACEM FLEXI SEALER** can be easily applied by using a brush or roller. On porous surfaces, dilute with 5% of water for the first coating. For the second coating, apply it undiluted. For optimum protection, a two coat application of **DURACEM FLEXI SEALER** is always recommended. Apply second coat as soon as first coat is tack free.

### SUITABLE SURFACES

**DURACEM FLEXIBLE SEALER** can be applied to concrete, brick, blockwork, asphalt, asbestos cement, natural stone, concrete roof tiles, cement render, roof-slates, iron, galvanized steel, etc.

### SPECIFICATIONS

**Color** : White, Light Grey  
**Binder** : Synthetic Resin  
**pH** : 10  
**Density** : 1.5kg/L

**Coverage** : 2-3m<sup>2</sup>/kg/mm<sup>2</sup>  
**Adhesion Strength** : 0.65N/mm<sup>2</sup>  
**Particle Size** : < 0.3mm  
**Drying time** : 30 minutes