

DURACEM SUPER RENDER 3 IN 1 331

三合一砖墙粗砂浆

DURACEM SUPER RENDER is a high quality cementitious render especially formulated for brick walls, hollowblock walls and concrete surfaces. It is intended to replace conventional cement-sand render. It is suitable for interior or exterior wall plastering and for brick laying purposes.

Mixing

Remove loose particles, grease and traces of foreign materials that may affect adhesion. Dry absorbent surfaces should be moistened before application of **SUPER RENDER**. Mix 1 bag (25kg) of **SUPER RENDER** with approximately 7.5L of water and mix thoroughly with an electric mixer or drum mixer for 3-7 minutes until the desired homogeneous paste is achieved.



用途

- 用来涂抹砖墙、空心砖墙及水泥墙面，使墙面平坦美观。也可以用来砌铺砖墙或铺补地板。

PRODUCT SPECIFICATION

Appearance	: Grey powder
Binder	: Cement
Filler	: Limestone
Additives	: Water soluble polymer to improve consistency, workability, water retention & adhesion
Potlife	: 3 - 4 hours
pH	: 12
Density	: • Dry: 1.2kg/L • Wet: 1.6kg/L
Specific gravity	: 1.5/cm ³
Coat thickness	: 2 - 3mm thick per layer of application
Coverage	: 1.2 kg/m ² / mm thick
Water consumption	: 7.5L / 25 kg bag
Adhesion to concrete	: 1.2MN/ m ²
Max aggregate size	: 0.75mm

PACKING AND STORAGE

Weight	: 25 kg/ bag
Shelf life	: 9 months
Storage	: Cool dry place

ADVANTAGES

- Consistent in ratio
- Mixes & applies easily
- Consistent quality
- High durability
- Good water resistant
- Contain anti-fungus properties
- Fast curing
- Anti-efflorescence
- Non- staining to tiles
- Better coverage
- Good shear adhesive strength

特性

- 适用于户内或户外的墙面
- 黏性佳，一抹即黏附于墙面
- 施工快速、减少浪费
- 施工后墙面平坦美观，不会有裂痕

APPLICATION



1. Add in water



2. Add in Super Render



3. Mix thoroughly



4. Apply to surfaces