



# 288 DURACEM WALLSKIM

# 墙面表层灰油

**DURACEM WALLSKIM 288** is a premixed plaster specially formulated for application onto freshly plastered cement sand plaster surface as a finishing coat, giving it a perfect smooth tough finish with no hairline cracks.

**DURACEM WALLSKIM 288** is ready for use. With its excellent workability and adhesion properties, it is the ideal alternative to the conventional cement-lime slurry mixture.

## MIXING & APPLICATION

Surface to be plastered must be sound, clean, free of loose particles, grease & traces of foreign materials that may affect adhesion. Mix 1 bag (25kg) of **DURACEM WALLSKIM 288** with approx 7.5L of water and mix thoroughly with an electric mixer or drum mixer for 3-5 minutes until the desired homogeneous paste is achieved. Apply onto surface manually using steel trowel or spatula. For best result, apply when the newly plastered substrate is still fresh.

## SPECIFICATIONS

Appearance	: Off Grey
Water Powder Ratio	: 0.33
Binder	: Portland Cement
Adhesion Strength	: >0.5N/mm <sup>2</sup>
Coat Thickness	: 2mm thick per layer
Coverage	: 1.5kg/m <sup>2</sup> /mm thick

## ADVANTAGES

- ▲ Smooth and durable finish
- ▲ Good Consistent quality
- ▲ Excellent workability and good adhesion
- ▲ No hairline cracks
- ▲ Easy to mix and apply