



DURALITE 水性室内乳胶漆 INTERIOR EMULSION PAINT

DURALITE EMULSION PAINT is a superior quality copolymer emulsion paint specially formulated for decoration and protection of interior surfaces.

DURALITE EMULSION PAINT dries to solid matt finish. It provides a durable coating on wall and ceiling, masonry surfaces, cement brickwork, plaster, asbestos, hard and soft boards.

SURFACE PREPARATION

Ensure the surface to be painted is clean, sound and dry, free of grease, oil and loosely adhering particles. For old and porous surfaces, apply one coat of **DURASEAL WALL SEALER**. All cracks and damaged surfaces should be repaired with suitable filler or **DURACEM PUTTY FILLER** which must be allowed to dry and harden prior to painting.

DIRECTION OF USES

- ▲ Stir well before use.
- ▲ Add 5-10% of clean water if thinning is necessary.
- ▲ Apply paint with brush, roller or spray. For better finish, apply two or more coats.
- ▲ Allow 1-2 hours drying time between coats
- ▲ Replace lid firmly after use and clean the painting equipment with water.

ADVANTAGES

- ▲ Easy to use
- ▲ Good opacity
- ▲ Excellent Coverage
- ▲ For interior surfaces
- ▲ Non Spatter