

DURACEM PLASTER BASE 238

底层砂浆

DURACEM PLASTER BASE is a high quality water resistant cementitious thin plaster specifically formulated for patching, repairing, leveling and surface improvement works to concrete and cement rendered surfaces. A hardened surface can be smoothed with **DURACEM PLASTER TOP**, painted or wall-papered. It is suitable for both interior or exterior application.

用途

- 适用于修补及抹平水泥墙面和混凝土天花板
- 可用于混凝土及沙灰墙面、空心砖墙、轻砖墙



PRODUCT SPECIFICATION

Appearance	: White / Grey
Binder	: Cement
Filler	: Limestone
Additives	: Water soluble polymer to improve consistency, workability, water retention & adhesion
Potlife	: 3 - 4 hours
pH	: 12
Density	: • Dry: 1.2kg/L • Wet: 1.6kg/L
Specific gravity	: 1.88/cm ³
Coat thickness	: 2 - 3 mm thick per layer of application
Coverage	: 1.5 kg/m ² / mm thick
Water consumption	: 7.5L / 25 kg bag
Adhesion to concrete	: 1.2MN/ m ²
Max aggregate size	: 0.5mm

PACKING AND STORAGE

Weight	: 25 kg/ bag
Shelf life	: 9 months
Storage	: Cool dry place

特性

- 施工快速，节省时间
- 节省成本
- 施工后墙面不会有裂痕
- 黏贴性强、只需薄薄一层
- 适用于户内或户外的墙面

APPLICATION



1. Add in water



2. Add in Plaster Base



3. Mix thoroughly



4. Apply directly to surface