

DURACEM TILE ADHESIVE is a high quality cement-based water resistant tile adhesive. With its excellent workability and adhesion properties, it is ideal for installation of ceramic wall/floor tiles, homogeneous tiles, quarry tiles, glass mosaic and mosaics on cement-based substrates.

DURACEM TILE ADHESIVE is suitable for both internal and external application.

瓷砖胶灰单组份聚合物改性防水瓷砖胶灰适合用于室内外墙砖及 地砖的铺设



Appearance: Fine white/ Grey powder

Binder : Portland Cement

Filler : Limestone/ graded silica sand
Additives : Water soluble polymer to improve

consistency, workability,

water retention & adhesion

Open time : Approx. 20min Potlife : Approx. 3 hours

pH : 12

Density : • Dry: 1.2kg/L • Wet: 1.6kg/L

Coat thickness : 2-3mm thick per layer of application Coverage : Approx. 2kg/m²/mm (with a notched

trowel of 4.5mm x 4.6mm notches)

Setting Time : • Initial - 6 hours

• Final - 7 hours

Compresitive Strength : 170kg/cm²
Water consumption : 8L / 25 kg bag
Adhesion to concrete : 1.2MN/ m²
Max aggregate size : 0.5mm

PACKING AND STORAGE Weight: 25 kg/ bag

Shelf life : 9 months
Storage : Cool dry place

DURACEM 多利盛 TILE ADHESIVE PEREKAT JUBN SPECIAL ST 798 WHITE ORLY WHITE ORLY

ADVANTAGES

- · Mixes & applies easily
- · Consistent quality
- High durability
- · Good water resistant
- · Contain anti-fungus properties
- · Eliminate the need to presoak tile
- Fast curing
- · Good shear adhesive strength
- Anti-efflorescence
- Non- staining to tiles
- Better coverage

特性

- 工厂预先混拌、品质确保一致性
- 操作性能好省时省力
- 黏附效果佳, 施工快速
- 瓷砖不须预先浸泡于水
- 瓷砖在粘结后的20分钟内还可调整
- 适合用来铺设瓷砖、磨石砖、玻璃磨石、 云石等

APPLICATION



1. Add water according to ratio



4. Apply on surfaces



2. Pour in Tile Adhesive 399



5. Shape using square/V notch



3. Mix thoroughly



6. Apply tiles